

Serial Number: 10/010,361
Art Unit: 3676

AMENDMENTS

Kindly amend the application as follows:

In the Abstract

/In the Abstract, line 8, please insert --is-- before "capable".

In the Claims

Claims 2, 3, 10 and 11, please cancel without prejudice to the subsequent filing of a continuing application.

Claims 1 and 10, please amend as follows:

1. (Amended) Apparatus comprising:

a handle having a key;

a piston having a bore;

a cam having first and second ends held by a cap for rotation in the bore, one of the first and second ends having a keyway capable of receiving the key; [and

a catch assembly that is capable of catching the key to the keyway]

a protuberance carried by one of the key and the cam

Serial Number: 10/010,361

Art Unit: 3676

at the keyway;

a detachably engageable recess carried by the other of
the key and the cam; and

an attached spring acting on the protuberance biasing
it one of:

a)away from the key; and

b)into the keyway.

Serial Number: 10/010,361

Art Unit: 3676

9. (Amended) Apparatus comprising:

a handle having a key;

a piston attached to an axle mounted to a hub, the piston having a bore;

a cam having first and second ends held by a cap for rotation in the bore, one of the first and second ends having a keyway capable of receiving the key; [and

a catch assembly that is capable of catching the key to the keyway]

a protuberance carried by one of the key and the cam at the keyway;

a detachably engageable recess carried by the other of the key and the cam; and

an attached spring acting on the protuberance biasing it one of:

a)away from the key; and

b)into the keyway.

Serial Number: 10/010,361

Art Unit: 3676

15. (Amended) Apparatus comprising:

a handle having a key;

a piston attached to an axle mounted to a hub attached to a bicycle wheel, the piston having a bore;

a cam having first and second ends held by a cap for rotation in the bore, one of the first and second ends having a keyway capable of receiving the key; [and

a catch assembly that is capable of catching the key to the keyway]

a protuberance carried by one of the key and the cam at the keyway;

a detachably engageable recess carried by the other of the key and the cam; and

an attached spring acting on the protuberance biasing it one of:

a)away from the key; and

b)into the keyway.